

TNR® offers rugged durability and high performance drive systems for large door sizes for:

## **HARSH ENVIRONMENTS**

dirt, dust, rain, snow, temperature

# **APPLICATIONS**

ideal for heavy industrial and commercial applications, sized for large equipment access

## **DOOR IMPACT CONCERNS**

easily handles lift truck and heavy vehicle impacts

# **HIGH WINDLOAD & PRESSURE DIFFERENTIAL**

caused by exterior wind & positive pressure work environments



Tough 'n' Ready
For Your Challenging
Environments

# **HDL** Heavy Duty Large

**Applications:** Heavy manufacturing, steel, pulp & paper, waste management, oil & gas and mining.

# TNR® leads the way with High Performance, Rugged Roll-up Doors for large openings

Big equipment needs big access openings. TNR® has the engineering and field experience that assures our custom built doors deliver peace of mind in your specific application.

### **TNR® Mechanical Features**

- $\bullet$  1/4" Black SBR rubber with polyester core weave. Flexible and resistant to abusive environments in temperatures from -40°F to +180°F.
- Patented NEWGEN® guide and Curtain Lok™ system. Reliable and consistent door operation. No guide gap maintenance required.
- Bottom bar with rubber loop.
- Sleek profile with easy installation, reduced clearances & minimal maintenance.
- No hinges, cables, pulleys or tension springs.
- Guide mounted thru-beam photoelectric sensor.
- Options: colors, windows, hoods, reversing edge, traveling windbar and MSHA-rated self-extinguishing curtains.

# **TNR® Drive Features**

- High Efficiency Helical Gear Head (HG) Operator with multi-function capacity PLC Control Panel.
- Options: access controls and specialty functions.

Standard Features	HDL23	HDL45
Opening Speed—Up to (inches per second)	20	18
Maximum Wind Resistance—88 mph (20 psf)	•	
<b>Type of Balancing</b> —Counterbalance spring assembly cycle rating (000)	50K	50K
Reversing Edge—Pressure sensitive wireless edge	•	
Control Panel—PLC or Relay Logic		
Activation—Remotes, pull cords, loop detectors		
Self Supporting Steel Frame—Steel Mounting Angle		
<b>Warranty</b> —Limited lifetime warranty on curtain and NEWGEN® Guide. Two years on all other parts and workmanship.	•	•

#### NEWGEN® Guide and Curtain Lok™ system







